








## IEC Connector Designations

| Connector                                                                           | IEC 320, EN 60 320<br>Standard Sheet Nos. |               | Max. Pin<br>Temperature | Max Rated Current<br>@ 250 Volt |          | Equipment<br>Class |
|-------------------------------------------------------------------------------------|-------------------------------------------|---------------|-------------------------|---------------------------------|----------|--------------------|
|                                                                                     | Male Inlet                                | Female Outlet |                         | UL/CSA                          | European |                    |
|    | C2                                        | C1            | 65°C                    | 0.2A                            | 0.2A     | II                 |
|    | C6                                        | C5            | 65°C                    | 2.5A                            | 2.5A     | I                  |
|    | C8                                        | C7            | 65°C                    | 2.5A                            | 2.5A     | II                 |
|    | C10                                       | C9            | 65°C                    | 6A                              | 6A       | II                 |
|    | C14                                       | C13           | 65°C                    | 15A                             | 10A      | I                  |
|   | C16                                       | C15           | 120°C                   | 15A                             | 10A      | I                  |
|  | C16A                                      | C15A          | 155°C                   | 15A                             | 10A      | I                  |
|  | C18                                       | C17           | 65°C                    | 10A                             | 10A      | II                 |
|  | C20                                       | C19           | 65°C                    | 20A                             | 16A      | I                  |
|  | C22                                       | C21           | 155°C                   | 20A                             | 16A      | I                  |
|  | C24                                       | C23           | 65°C                    | 20A                             | 16A      | II                 |